




**RoHS**


Organic silicon free

Phosphorus-free

### ORDERING CODE (命名规则)



### FEATURES (产品特点)

- PCB mounted switching Power module
- AC input voltage range: 90VAC-264VAC
- DC input voltage range: 100VDC-370VDC
- Ambient temperature range: -25°C ~70°C
- Storage temperature range: -25°C ~85°C
- Leakage current (input :264VAC): <0.3mA
- Isolation voltage: input –Output  $\geq 3600\text{VAC}$  60s
- Insulation Resistance: Input –Output  $500\text{VDC} \geq 100\text{M Ohms}$
- MTBF: 300Khrs Min MIL-HDBK-217F (25°C)
- Compact size, easy installation
- High efficiency low standby Power consumption, green environmental protection function
- Built-in output over current protection, over-voltage protection, short circuit protection
- Built-in EMI filter components, comply with the EN55032 class B standard
- Class II Construction 

### APPLICATIONS (应用)

This series could be widely applied in the LED, light control, Instrument, smart home and other home appliances.



### MODEL LIST (型号列表)

Model No.	Output Power	DC Voltage	Rated Current	Efficiency 230VAC, % Typ.	Ripple & Noise (max)	Ambient TEMP(°C)	Weight	Certificate		
								UL	TUV	CB
ZPL15S0500WL-1SF	15W	5Vdc	3000mA	78%	<200mV	50	65g	●	●	●
ZPL15S1200WL-1SF	15W	12Vdc	1250mA	82%	<200mV	50	65g	●	●	●
ZPL15S1500WL-1SF	15W	15Vdc	1000mA	82%	<200mV	50	65g	●	●	●
ZPL15S1800WL-1SF	15W	18Vdc	830mA	83%	<200mV	50	65g	●	●	●
ZPL15S2400WL-1SF	15W	24Vdc	620mA	83%	<200mV	50	65g	●	●	●


### ELECTRICAL SPECIFICATION (电性能参数)

Model No. / 型号		ZPL15SXX00WL-1SF		
Input 输入参数	Rated Voltage / 额定电压	100-240VAC		
	Voltage Range / 输入电压范围	90-264VAC or 100-370VDC		
	Frequency (Hz) / 输入频率范围	47-63 Hz		
	Current (Full load) / 输入电流	115VAC	230VAC	
		300mA	200mA	
	Inrush Current (<500us) / 冲击电流	20A	40A	
	No Load Loss / 待机功耗	0.3W max. @230VAC		
HOT PLUG / 热拔插	Unavailable			
Output 输出参数	Voltage (V) / 输出电压	Refer to "Model List"		
	Current (mA) max. / 输出额定电流	Refer to "Model List"		
	Voltage Accuracy / 输出电压精度	±3%		
	Line Regulation / 线性调节率	±0.5%		
	Load Regulation / 负载调节率	±1%		
	Minimum Load (mA) / 最小负载	0		
	Ripple & Noise / 输出纹波	Refer to "Model List"		
	Efficiency (typ.) / 工作效率	Refer to "Model List"		
	Start-up Time / 开机延迟时间	3s		
Hold up Time / 掉电保持时间(典型值)	76.9ms/230VAC ,13.6ms/115VAC			
Protection 保护特性	Over Current Protection / 过流保护	Hiccup mode		
	Short Circuit Protection / 短路保护	Hiccup mode		
Environment 环境	Operating Temperature / 工作温度	-25°C...+70°C @free air convection (refer to the Power Derating Curve)		
	Operating Humidity / 工作湿度	20~90% RH ( No Condensing) at full load		
	Storage Temperature / 存储温度	-25°C~85°C		
	Storage Humidity / 存储湿度	10~95% RH		
	Temperature Coefficient/温度漂移系数	±0.05%/°C (0~50°C)		
Physical 外观结构	Case Material / 外壳材质	Plastic (UL 94V-0 rated)		
	Weight / 产品净重	65g (ref.)		
Safety & EMC 安全认证及 电磁兼容	Dielectric Strength / 绝缘强度	I/P-O/P : 3600VAC		
	Protection against electric shock	Class II construction <input type="checkbox"/>		
	Safety Standards / 安全标准	Compliance with EN62368-1, EN61558-2-16, Plastic materials in accordance with EN60335-1 clause 30		
	EMI / 电磁兼容	Compliance with EN55032 CLASS B, EN61000-3-2, EN61000-3-3		
EMS (Noise Immunity)/ 电磁抗干扰	Compliance with EN55035	Need to add external EMC component (Refer to the Schematic)		
Reliability Requirement 可靠性要求	MTBF/平均故障间隔时间	300Khrs Min MIL-HDBK-217F (25°C)		
	Burn-In Test/ 老化测试	The unit shall be burned in for 2~4 Hours under 240Vac input and with full load at 25°C		

## PRODUCT CHARACTERISTIC CURVE (产品特性曲线)



## TYPICAL APPLICATION SCHEMATIC (典型应用电路)



ITEM	MOV	FUSE
1~2W	14D561K	1A/250V
3-10W	14D561K	2A/250V
10~20W	14D561K	3.15A/250V

Note: External circuit components are only recommendations, customers should choose their own components and values according to their specific system application requirements.

## MECHANICAL SPECIFICATION (尺寸图)

